CASIO

Smile! CASIO offers practical management solutions for your business

TE-2200

Electronic Cash Register

TE-2200 / TE-2400

http://world.casio.com

Simple yet powerful features and functions increase efficiency of store management and improve productivity

Receipt and journal printer

58mm wide thermal printers equipped with the capability of graphic logo and watermark, double-height printing for receipts, compressed printing mode for journal printing and a printing speed of 14 lines per second. Drop-in paper loading for easy handling of paper replacement.

Display

5.2-inch LCD operator display (2 lines x 16 characters, 7-segment digits for display of amounts) with backlight. Contrast is adjustable for easy readability. Equipped standard with pop-up customer display.

Help function

The blue circle on the keyboard marked as "HELP" can print guidance messages on the receipt printer which contain answers to frequently asked questions such as how to program the time and date. Furthermore, these messages are customizable to meet individual needs.



Data storage for your sales reports and program data backup

A CF (Compact Flash) card can be used as a storage device for sales data to create your reports with spreadsheet software to make creating sales reports much easier. A CF card can store program data for backup purposes as well.

Peripherals

Two serial ports are available for direct connection to a PC, external remote printer, modem for connecting to head office, scanner for barcode reading, or slip printer for printing guest reciepts or validation.

Barcode reading function

The function for direct entry of items not found eliminates the time necessary for searching for new items, thus reducing queues at the register. Items can be added to the master file directly using the associated department name. Direct and batch maintenance functions in the program mode are also available for further processing. The master file can handle newly introduced items according to your program and can be optimized using the inactive items report.

Table control function

Basic table control function is provided for small restaurants, cafés and bars. External printer can be configured for order or receipt printing.

OTHER USEFUL FUNCTIONS

- Clerk interrupt function
- Scheduler function
- Set menu function
- Backlight turns off automatically when timer is programmed
- Arrangement function
- Memory allocation function

REPORTS

- Financial
- Transaction
- Department
- PLU
- PLU stock
- Table analysis
- Open check
- Monthly
- Hourly
- Flash
- Group
- Clerk
- Time & attendance
- Scanning PLU
- Scanning PLU stock
- Inactive PLU



OPTIONS

Model No.	Product
SP-1300	Slip printer
UP-360	External printer
HHS-15	Hand-held barcode scanner

SPECIFICATIONS

Displays	Operator	5.2-inch backlit LCD 2 x 16 characters / 10 digits, 7 segments
	Customer	Pop-up 8-digit numeric LED
Printer	Printing method	Two-station thermal printer
	Printing speed	14 lines/sec. (max.)
	Paper width	58mm +0/-1mm x 80ϕ
	Paper-loading	Drop-in paper-loading
Memory backup		90-day data backup(vanadium lithium battery)
Power consumption	AC 120V	Operating 0.5A, Standby 0.1A
	AC 230V	Operating 0.25A, Standby 0.05A
Operating environment	Temperature	0 to 40℃
	Humidity	10 to 85%RH
Dimensions (W x D x H)		400 x 450 x 277(331)*mm
Weight		Approx. 12 kg

*Includes pop-up customer display height.

TE-2400

Full flat keyboard model with 77 Flat-PLU keys

http://world.casio.com

NOTE: Specifications and design subject to change without notice.

CASIO

CASIO COMPUTER CO., LTD.
Tokyo, Japan